

DS-K1T671MF Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in Mifare card reading module
- Face recognition distance (without face mask): 0.3 m to 3 m, Duration < 0.2 s/User, Accuracy rate ≥ 99%
- Max.6000 faces, Max.6000 cards and Max. 5000 fingerprints
- Two-way audio with client software, indoor station, and main station
- Supports TCP/IP
- Configuration via the web client
- Supports ISAPI and ISUP5.0 protocol
- IP65



▪ Specification

System	
Operation system	Linux
Display	
Dimensions	7-inch
Type	LCD
Operation method	Capacitive touch screen
Video	
Pixel	2 MP
Lens	2
Audio	
Tone quality	Noise suppression and echo cancellation
Network	
Wired network	10 M/100 M/1000 M self-adaptive
Interface	
Network interface	1
RS-485	1
Wiegand	1
Lock output	1
Exit button	1
Door contact input	1
IO input	2
IO output	1
Power interface	2-pin
TAMPER	1
USB	2
Capacity	
Card capacity	6000
Face capacity	6000
Fingerprint capacity	5000
Event capacity	50,000
Authentication	
Card type	Mifare 1 card
Card reading frequency	13.56MHz
Card reading distance	0 to 5 cm
Face recognition accuracy rate	≥ 99%
Face recognition distance	0.3 to 3 m (Without face mask)
Fingerprint recognition duration	≤ 1 s
Function	
QR code recognition	Support
Face anti-spoofing	Support
Advertisement	Support
Audio prompt	Support
Time synchronization	Support

General	
Power supply method	2-pin connecter
Power supply	12 VDC/2 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	10 to 90% (No condensing)
Dimensions	290 mm × 116.5 mm × 33 mm (11.4" × 4.6" × 1.3")
Protective level	IP65
Installation	Surface
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)
Platform	Hik-ProConnect and HikCentral Professional

▪ Available Model

DS-K1T671MF

▪ Dimension



▪ Accessory

▪ Optional

DS-KAB671-P1	DS-KAB671-S Protective Shield	DS-KAB671-S Protective Shield	DS-KAB671-B Stand Stick	DS-KAB671-B Stand Stick
				
DS-K3H4411-120		DS-K3H4410-120		
				

Distributed by



HIKVISION

Headquarters

No.555 Dianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-856-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-29486900
sales@pram@hikvision.com

Hikvision Canada
T +1-866-250-8690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-0949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0458-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-8050
latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7852-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-802140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (11) 0351172
saafrica@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-8730667
nikia.pantlov@hikvision.ru

Hikvision Vietnam
T +84-974270808
sales.vt@hikvision.com

Hikvision UAE
T +971-4-8432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-8438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1781
info.hk@hikvision.com

Hikvision Russia
T +7-495-860-67-90
salesru@hikvision.com

Hikvision Korea
T +82-10331-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com