

RG-EW300R 300Mbps Wi-Fi Extender

DATASHEET



Highlights

- Plug and play, easy and strong
- Two built-in signal amplifiers boost 1.5X signal strength
- Three-bar signal indicator guides you to find the best spot
- Flexible placement, one-click connection
- Take control of your home network at your fingertips

Highlight Features









Three-bar Signal Indicator Guides You to Find the Best Spot

EW300R clearly shows you the signal strength and guides you the best spot to position the repeater, while others only give you the "Yes or No" answer.


/ Highlight Features













	Basic
Dimensions (W×D×H)	92 mm x 70 mm x 38 mm (3.62 in. × 2.76 in. × 1.50 in. antennas not included)
Weight	0.14 kg (packages not included)
Wi-Fi Standards	Wi-Fi 4 (802.11n)
MIMO	2.4 GHz, 2×2, MIMO
Max. Wi-Fi Speed	2.4 GHz: 300 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz
Antennas	2
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 4 dBi
Port	1×10/100 Base-T WAN/LAN
Recommended Users	8
Max. Users	16
Power Supply	100-240V~50/60Hz 0.5A
Power Consumption	≤12W
Operation Frequency Bands	802.11b/g/n: 2.412 GHz to 2.472 GHz country-specific restrictions apply
Transmit Power	<20 dBm (2.4 GHz) country-specific restrictions apply
Operating Temperature	-10 °C to +45 °C (14 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE,RoHS
OFDMA	-
MU-MIMO	-

	Wireless	
BSS Coloring	-	
Maximum Number of SSIDs	3	
SSID Hiding	✓	
Band Steering	-	
Guest Wi-Fi	✓	
WPA/WPA2	✓	
WPA3	-	
Roaming	-	
Blacklist	~	
Reyee Mesh	-	
Mesh Pairing by Hardware	-	
Mesh Pairing by Mesh Button	-	
Mesh Pairing by Eweb	-	
Recommended Hop Count	-	
Wi-Fi Optimization	✓	
QoS (WMM)	-	
WPS	✓	
Transmission Power Adjustment	✓	
Hardware Control of the Control of t		
CPU	MT7628DAN	
Flash	16 MB	
RAM/SDRAM	64 MB	
Color	White	

Hardware		
System LED Indicator	✓	
Reyee Mesh LED Indicator	-	
Reyee Mesh Button	-	
Power Button	-	
Reset Button	✓	
DC Connector Dimensions	-	
	WAN	
Static IP	✓	
DHCP	✓	
PPPoE	✓	
Learning PPPoE Account & Password	-	
VLAN Tagging	✓	
	LAN	
DHCP Server	✓	
Client List	~	
Static IP Assignment	✓	
Port-Based Flow Control	-	
	Features Programme Control of the Co	
TR069	✓	
IPv6	~	
DDNS	-	
IPTV	-	
Alarm	-	
Diagnosis	-	

	Features	
UPnP	-	
ARP Binding	-	
Port Mapping	-	
DMZ Host	-	
Rate Limitation of Terminals	-	
Hardware Acceleration	-	
MAC Address Cloning	✓	
Cloud Management	✓	
Repeater Mode	✓	
WISP Mode	✓	
	Security	
PPTP VPN Server	-	
PPTP VPN Client	-	
L2TP VPN Client	-	
Parental Control	-	
Protect TCP Flood Attacks	✓	
Protect ICMP Attacks	-	
Protect UDP Flood Attacks	-	
System		
Default Access/Password	10.44.77.254 No Password Required by Default	
URL Access	-	
Local Upgrade	✓	
Online Upgrade	✓	

System	
APP Upgrade	✓
Syslog	-
Backup	
Factory Reset	✓
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

Package Contents

Device	RG-EW300R
Wireless Extender	1
User Manual	1
Warranty card	1



Redefine your easy network

Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Website: https://reyee.ruijie.com/en-global